



SPRUCE RB SERIES INLINE FANS SPECIFICATIONS



RB SERIES TECHNICAL SPECIFICATIONS

The Spruce RB Series fans are rated for both residential and commercial use. The durable, corrosion-resistant engineered thermoplastic fan housing makes RB fans ideal for duct boosting and bathroom, living area and garage ventilation. These remotely mounted fans, unlike ceiling or wall-mounted fans, can silently draw from multiple intake points, such as over a bathroom tub, sink and toilet.


MODEL	P/N	DUCT	WATTS	TYPICAL CFM VS. STATIC PRESSURE						
				0"	0.2"	0.5"	0.75"	1"	1.25"	1.5"
RB110	28128	4"	14-20	121	100	68	28	---	---	---
RB275	28115	6"	53-79	272	230	176	138	103	57	13
RB300	28088	6"	66-87	318	280	211	170	135	87	30
RB350	28261	8"	91-129	334	299	247	210	176	142	116
RB400	28206	8"	95-152	497	450	353	281	220	176	130
RB500	28207	10"	99-152	542	500	420	344	275	219	165

Spruce RB fans are suitable for bathroom ventilation, duct boosting, and garage ventilation.

MADE IN USA Made in USA with U.S. and imported parts.

ETL ETL Listed
Intertek

5 YEAR All Spruce™ inline fans are covered by our 5-year, hassle-free warranty.



Features

- Durable thermoplastic housing
- Virtually silent
- Energy efficient
- Remote mounting
- Multiple intake locations
- Rated for commercial or residential installations
- Rated for continuous operation
- Five-year warranty

Model	H	h	D	d
RB100	8.5"	1"	9.7"	4"
RB275	8.6"	1"	11.8"	6"
RB300	9"	1"	13.4"	6"
RB350	9"	1"	13.4"	6"
RB400	10.5"	1"	13.4"	8"
RB500	10.5"	1"	13.4"	10"



02077 Rev A



#2 Chootoo Road, South Aranguez, San Juan, Trinidad

