

# **CANARM - WREN - PENDANT LIGHTING** SPECIFICATION SHEET



## PENDANT LIGHT

IPL702A01 11/17

QUESTIONS OR CONCERNS CONTACT AT: 1-800-265-1833 (English) / 1-800-567-2513 (French) Monday through Friday 8:00 AM to 5:00 PM E.S.T.



INSTRUCTIONS PERTAINING TO RISK OF FIRE OR INJURY TO PERSONS READ ALL INSTRUCTIONS

IMPORTANT SAFETY **INSTRUCTIONS** SAVE THESE INSTRUCTIONS

## TOOLS AND MATERIALS REQUIRED:






Wiring supplies as required by local electrical code

### **SAFETY PRECAUTIONS:**


- 1.TURN OFF ELECTRICAL POWER BEFORE STARTING INSTALLATION OF LIGHT FIXTURE.
- 2. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.
- 3. CONNECT THE GROUND WIRES (BARE COPPER OR GREEN) FROM YOUR FIXTURE TO THE GROUND WIRE (BARE COPPER OR GREEN) OR GROUND SCREW IN THE ELECTRICAL BOX.
- 4. TO CLEAN THE FIXTURE, TURN OFF THE POWER, WAIT FOR IT TO COOL, AND WIPE THE FIXTURE WITH A CLEAN, SOFT CLOTH.

NOTE: Product may not look exactly as shown in figures.


### **INSTALLATION:**




1 Loosen "B". Adjust stud to desired length and lock in place with "B"



2. Mount the mounting bracket to electrical box using electrical box screws (not included). Make sure the studs on the mounting bracket are facing out from the electrical hox




 $4_{\circ}$  Connect the ground wires (bare copper or green) from your fixture to the ground wire (bare copper or green) or ground screw in the electrical box. Connect the black wire from the fixture to the black wire in the electrical box and connect the white wire from the fixture to the white wire in the electrical box.



 $\mathbb{G}_{\circ}$  Install the light fixture to the ceiling by aligning the holes in the fixture with the studs on the mounting bracket. Secure fixture in place with star washers and cap nuts.

 $\mathbb{Z}_{\circ}$  Install proper bulb type and wattage (not included).



 $\mathbb{S}_{ullet}$  Adjusting the length of flexible cord. For safety, do not release the knot inside canopy.

Tel: (613) 342-5424, Fax: (800) 263-4598

Bulb











