

CANARM - MALENE - MOUNTED LIGHTING INSTALLATION GUIDE



SEMI-FLUSH

ISF1079A03 10/20

NEED HELP? Call or Email us first

Our service team is ready to answer your questions... 1-800-265-1833 (English) / 1-800-567-2513 (French) IN CANADA - ressalescanada@canarmna.ca - IN USA - ressalesusa@

Monday – Friday



INSTRUCTIONS PERTAINING TO RISK OF FIRE OR INJURY TO PERSONS READ ALL INSTRUCTIONS IMPORTANT SAFETY

INSTRUCTIONS SAVE THESE INSTRUCTIONS




Wire Cutters

Wiring supplies as required by local electrical code


- **SAFETY PRECAUTIONS:** 1. TURN OFF ELECTRICAL POWER BEFORE STARTING INSTALLATION OF LIGHT FIXTURE.
- 2. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.
- 3. CONNECT THE GROUND WIRES (BARE COPPER OR GREEN) FROM YOUR FIXTURE TO THE GROUND WIRE (BARE COPPER OR GREEN) OR GROUND SCREW IN THE ELECTRICAL BOX.
- 4. TO CLEAN THE FIXTURE, TURN OFF THE POWER, WAIT FOR IT TO COOL, AND WIPE THE FIXTURE WITH A CLEAN, SOFT CLOTH.

NOTE: Product may not look exactly as shown in figures.


INSTALLATION:




 $\mathbb{1}_{\circ}$ Screw the center rod and canopy to the fixture.



 \mathbb{Z}_{\circ} Loosen "B". Adjust stud to desired length and lock in place with "B"




 \mathfrak{Z}_{\circ} Mount the mounting bracket to electrical box using electrical box screws (not included). Make sure the studs on the mounting bracket are facing out from the electrical hox.



5. Once connections of wires are completed, carefully tuck wires and wire nuts into the electrical box making sure no bare wire (on the black and white) is visible at the wire nuts.

6. Position fixture over study on mounting bracket assembly. Secure fixture in place with star washers and cap nuts.

 \mathbb{Z}_{\circ} Install specified bulb type and wattage (not included).



4. Connect the ground wires (bare copper or green) from your fixture to the ground wire (bare copper or green) or ground screw in the electrical box. Connect the black wire (or wire with marking) from the fixture to the black wire in the electrical box and connect the white wire from the fixture to the white wire in the electrical box.

Tel: (613) 342-5424, Fax: (800) 263-4598











